



GETELEC

We protect your electronics


# GRAPHITE NICKEL FILLED CONDUCTIVE FLUOROSILICONE - GT 3107

GT 3107 is a graphite nickel filled conductive fluorosilicone elastomer which enables the creation of sealed, conductive gaskets, which can come into contact with solvents, oils, hydrocarbons or hydraulic fluids.

- Good low-frequency performance
- Stable electrical properties
- Grade compliant with UL 94 V0
- Economical solution
- Excellent resistance to oils and hydrocarbons



Properties	Standards - Test	GT 3107
Type MIL G 83528		-
Elastomer binder		Fluorosilicone
Conductive filler		Graphite nickel
Volume Resistivity $\Omega \cdot \text{cm}$	MIL G 83528	< 0.10
Hardness shore A	ASTM D 2240	65
Density $\text{g/cm}^3$	ASTM D 792 Method A	2.30
Break resistance Mpa	ASTM D 412 Method A C	1.30
Elongation at break %	ASTM D 412 Method A C	200
Tear resistance N/mm	ASTM D 624 C	6.08
Residual deformation after 70 hours of compression at 100°C	ASTM D 395 Method B	25
Continuous usage temperature		-55°C to +150°C
Color		Dark grey



## AVAILABLE FORMATS

- Molded
- Cut
- Extruded
- Sheet
- Vulcanization bonding

